## SINGLE BOARD COMPUTER R-SERIES





R-Series features the NXP i.MX RT Cortex M7 Cross Over MCU. R-Series SBC targets cost sensitive customers, providing a graphical-touch and gesture-optimized, Human-Machine-Interface (HMI).

R-Series can be expanded to support other applications with the expansion port features, CAN and RS485 buses.



## **Feature Rich**



**Easy Integration** 



## Compact

	: MV DT 4064 Contay M7 @ 600 MU
MCU	i.MX RT 1064, Cortex-M7 @ 600 MHz
	4MB On-Chip Flash, 1MB On-Chip SRAM
Memory	32MB SDRAM and 8MB QSPI Flash
Wifi with BT	Single band 802.11 a/b/g/n BT 4.2
USB	1 USB 2.0 Host, 1 USB 2.0 OTC
Interface	SD Card, RTC, CAN, RS485
	Expansion port – USB, I2C, 3X GPIO, UART, PWM
Audio	Support up to 10W speaker
Display	LCD display controller (up to WXGA 1366x768)
	Support 4.3", 5"and 7" LCD
	Capacitive touch panel
Security IC	Hardware key encryption & management or 16Kb EEPROM
Software	Free RTOS or Baremetal
Graphical UI	QT for MCU or LVGL (Light Versatile Embedded Graphics library)
Dimensions	125mm x 90mm

